Pouces et Métrique Tampons

WELL-NUT®

Well-Nut is essentially a bushing of tough neoprene having a flange at one end and a brass nut captive within the bore at the other.

Tightening a conventional machine screw engaging the

captive nut causes the

bushing to expand—against the inner side of a thin-wall material, or against the sides of a blind hole in solid material—effecting a secure fastening. Available in a variety of formulations, Well-Nut resists most environmental conditions.

WHAT IT IS... Tough! NEOPRENE HOW IT INSTALLS...



 Well-Nut is inserted in a pre-drilled hole, with its flange against the outer surface. Since Well-Nut is a blind fastener, it is installed from one side of the work with no need for access to the inner side.




2. The part to be assembled to the surface isplaced against the flange of the Well-Nut, and is secured by a machine screw engaging the captive brass nut.



3. As the machine screw is tightened, the neoprene body of the Well-Nut is compressed and expanded, forcing it tightly into the screwthreads and against the inner surface of the thin wall material.



4. Installed in a blind hole in solid material, the body of the Well-Nut expands tightly against the walls of the hole, effecting a secure, dependable fastening.



DIMENSIONS & INSTALLATION DATA

No other blind fastener doesallthis...

- Fastens in thin walls or blind holes.
- Functions as a threaded insert, or a fastener, or both.
- Seals effectively against air or liquid leakage at the assembly joint.
- Muffles noise.
- Dampens vibration, absorbs shock.
- Insulates electrically.
- Prevents galvanic corrosion.
- Ideal fastener for plastic-tometal and other dissimilar materials.

SPAENAUR No.	E THREAD SIZE	A HEAD DIA.	B O/A LENGTH	C LENGTH UNDER HEAD	D BODY DIA.	F HEAD HEIGHT	RECOM- MENDED HOLE SIZE	GRIP RANGE	UNIT PKG. QTY.
102-200	6-32	.452	.499	.437	.312	.062	5/16	.015156	50
102-201	6-32	.554	.981	.946	.240	.035	1/4	.375607	50
102-202	8-32	.438	.499	.447	.312	.052	5/16	.015156	50
102-203	10-24	.562	.562	.437	.375	.125	3/8	.015050	50
RB-312	10-24	.562	1.551	1.500	.375	.051	3/8	.812-1.143	50
102-204	10-32	.500	.554	.518	.375	.036	3/8	.015192	50
102-205	10-32	.562	1.051	1.000	.375	.051	3/8	.312643	50
102-206	10-32	.750	.807	.620	.375	.187	3/8	.030227	50
102-207	10-32	.750	.700	.620	.375	.080	3/8	.030227	50
102-209	10-32	.562	.665	.625	.375	.040	3/8	.035232	50
102-210	10-32	.554	.847	.812	.375	.035	3/8	.312450	50
102-211	1/4-20	.630	.630	.579	.500	.051	1/2	.015111	50
102-217	M6x1.0 mm	.750	.829	.642	.500	.187	1/2	.031187	50
102-212	1/4-20	.750	.829	.642	.500	.187	1/2	.031187	25
102-213	1/4-20	.635	1.051	1.000	.500	.051	1/2	.250457	25
RB-314	1/4-20	.630	1.395	1.384	.500	.051	1/2	.275422	25
102-214	5/16-18	.875	.725	.600	.620	.125	5/8	.015156	10
102-215	3/8-16	1.250	1.062	.875	.750	.187	3/4	.015437	10

WELL NUT® ASSORTMENT

ASSORTMENT ASSORTIMENT

805-544

Priced Singly

16 Sizes — 140 Pieces

Furnished in Regular Size grey enamel Steel drawer with scooped bins for easy access.

Drawer will fit into Slide Racks shown on page A2.

Shipping Weight: 2.43 kg (5.36 lbs.)

The quantities of each number are as follows:

SPAENAUR	Ass't.	SPAENAUR	
No.	Qty.	No.	
102-200	10	102-209	
102-201	10	102-210	
102-202	10	102-211	
102-203	10	102-212	
102-204	10	102-213	
102-205	10	102-214	
102-206	10	102-215	
102-207	10	RB-314	

CATALOG 13

Ass't.

Qty.

10

10

10

5

5

5 10